

Safety Data Sheet

Version 4

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier	
Product name	CHAMPION SPRAYON CARPET & UPHOLSTERY FOAMING CLEANER
Chemical name	7-7976-5
Other means of identification	
Product code	FG 438-5148-12
Synonyms	Carpet and upholstery cleaner
Recommended use of the chemical	and restrictions on use
Recommended Use	Carpets and upholstered surfaces.
Uses advised against	DO NOT USE ON FLOORS
Details of the supplier of the safety	data sheet
Supplier Address	Manufacturer Address
Chase Products Co.	Chase Products Co.
2727 Gardner Road	2727 Gardner Road
Broadview, IL 60155	Broadview, IL 60155
708-865-1000	708-865-1000
Emergency Telephone Number	
Company Phone Number	708-865-1000
24 Hour Emergency Phone Number	1-800-255-3924
Emergency telephone	ChemTel 1-800-255-3924

2. Hazards Identification

Classification

FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

Odor	Clean, floral
	Odor

Precautionary Statements - Prevention Keep away from heat, sparks, open flames and hot surfaces. — No smoking Pressurized container: Do not pierce or burn, even after use

Do not spray on an open flame or other ignition source

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

Hazards not otherwise classified (HNOC)

Other Information

· Harmful to aquatic life with long lasting effects

Harmful to aquatic life

0% of this mixture consist of ingredient(s) of unknown toxicity.

3. Composition/information on Ingredients

Common Name	Carpet and upholstery cleaner.
Synonyms	Carpet and upholstery cleaner.
Chemical Family	MIXTURES.
Formula	7-7976-5
Chemical nature	Aqueous solution of surfactants and cleaners.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	85-90	*
N-Butane	106-97-8	1-5	*
Sodium Lauryl Sulfate	151-21-3	1-5	*
Propane	74-98-6	1-5	*
2-Butoxyethanol	111-76-2	<1	*
Sodium Lauroyl Sarcosinate	137-16-6	<1	*

Chemical Additions Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures				
FIRST AID MEASURES				
Eye Contact	Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.			
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician.			
Inhalation	If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artifical respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.			
Ingestion	Ingestion from an aerosol product is unlikely to occur.			
Most important symptoms and effe	cts, both acute and delayed			
Symptoms	Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation. Chronic: 2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney damage.			

Indication of any immediate medical attention and special treatment needed

Note to physicians

None needed.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame. Sensitivity to Static Discharge Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures				
Personal precautions	Use with adequate general or local exhaust ventilation.			
For emergency responders	Remove all sources of ignition.			
Environmental precautions				
Environmental precautions	See Section 12 for additional Ecological Information.			
Methods and material for containn	nent and cleaning up			
Methods for Containment	Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.			
Methods for cleaning up	Clean contaminated surface thoroughly.			
7. Handling and Storage				
Precautions for safe handling				
Advice on safe handling	Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.			
Conditions for safe storage, including any incompatibilities				
Storage Conditions	Store in a cool, dry place away from heat and open flame. Keep out of reach of children. AEROSOL STORAGE LEVEL I (NFPA-30B) .			
Incompatible Materials	Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.			
8. Exposure Controls/Personal Protection				
Control parameters				
Exposure guidelines	See occupational exposure limits listed below.			

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
N-Butane 106-97-8	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m³
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³

Appropriate engineering controls

Engineering controls

Use with adequate general or local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face Protection	Conventional eyeglasses to guard against splashing.
Skin and Body Protection	Rubber, vinyl or household type gloves required.
Respiratory protection	Use in a well-ventilated area ONLY. WHEN USING INDOORS, KEEP WINDOWS AND DOORS OPEN UNTIL FUMES DISSIPATE.
General hygiene considerations	Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Appearance Color	Aerosol Cloudy, light yellow liquid light yellow	Odor Odor threshold	Clean, floral No information available
<u>Property</u> pH Melting point/freezing point Boiling point/boiling range	<u>Values</u> 9.48 Not applicable Water 212 °F/100 °C	Remarks • Method No information available No information available No information available	
Flash Point	Not applicable. This is an foam aeroso that when tested for flammability the flame duration is 7 seconds or more and the flame height is 4 cm or more.		
Evaporation Rate Flammability (solid, gas) Flammability Limits in Air	Faster than butyl acetate	No information available No information available No information available	
Upper flammability limits Lower Flammability Limit Vapor pressure	Not available Not available	No information available	
Vapor Density Relative Density Water solubility Solubility in other solvents Partition coefficient Autoignition Temperature Decomposition temperature Kinematic viscosity Dynamic viscosity	1.00 concentrate	No information available No information available Soluble in water No information available No information available No information available No information available No information available No information available	
Explosive properties	No information available		

Oxidizing properties

No information available

Other Information

Softening point Molecular weight VOC content (%) Density Bulk Density No information available No information available 4.96 8.33 lb/gal No information available

10. Stability and Reactivity

Reactivity Not applicable

Not applicable

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong alkali and strong oxidizing agents.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Product Information	This product has not been tested as whole. See below for information on ingredients.
Inhalation	Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and nausea.
Eye Contact	Can cause irritation after contact with eyes.
Skin contact	May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.
Ingestion	This is an aerosol product, ingestion is unlikely to occur. 2-Butoxyethanol may cause red

 Chemical name
 Oral LD50
 dermal LD50
 Inhalation LC50

 Water
 > 90 mL/kg (Rat)

 7732-18-5

-	-	= 658 g/m ³ (Rat) 4 h
= 1288 mg/kg (Rat)	= 200 mg/kg (Rabbit)	> 3900 mg/m ³ (Rat) 1 h
· ·	·	
-	-	> 800000 ppm (Rat) 15 min
= 470 mg/kg (Rat)	= 435 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
		= 486 ppm (Rat) 4 h

Information on toxicological effects

Symptoms	Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and
	nausea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily. Frequent or wide spread contact may results on skin absorption of potentially harmful amounts.
Serious eye damage/eye irritation	Irritating to eyes.
corrosivity	Not applicable.
sensitization	No a skin sensitizer.
Germ cell mutagenicity	No information available.
Carcinogenicity	Not known chronic effects based on available data. None of the ingredients present in excess of 0.1% are listed as carcinogenic by NTP, IARC or OSHA.

Chemical name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol	A3	Group 3		
111-76-2		-		

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration Hazard	Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and
	nausea.

Numerical measures of toxicity - Product Information

Unknown acute toxicity	0% of this mixture consist of ingredient(s) of unknown toxicity.
The following values are calculated	based on chapter 3.1 of the GHS document
ATEmix (oral)	45231 mg/kg
ATEmix (dermal)	26852 mg/kg
ATEmix (inhalation-gas)	7402695 mg/l
ATEmix (inhalation-dust/mist)	45.1 mg/l
ATEmix (inhalation-vapor)	15076 mg/l

12. Ecological Information

ecotoxicity

6.1% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Sodium Lauryl Sulfate 151-21-3	3.59 - 15.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 30 - 100: 96 h Desmodesmus subspicatus mg/L EC50 117: 96 h Pseudokirchneriella subcapitata mg/L EC50 53: 72 h Desmodesmus subspicatus mg/L EC50	 10.2 - 22.5: 96 h Pimephales promelas mg/L LC50 semi-static 10.8 - 16.6: 96 h Poecilia reticulata mg/L LC50 static 13.5 - 18.3: 96 h Poecilia reticulata mg/L LC50 semi-static 15 - 18.9: 96 h Pimephales promelas mg/L LC50 static 22.1 - 22.8: 96 h Pimephales promelas mg/L LC50 static 4.06 - 5.75: 96 h Lepomis macrochirus mg/L LC50 static 4.2 - 4.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 4.3 - 8.5: 96 h 		1.8: 48 h Daphnia magna mg/L EC50

FG 438-5148-12 CHAMPION SPRAYON CARPET & UPHOLSTERY FOAMING CLEANER

	Oncorhynchus mykiss mg/L LC50 static		
	5.8 - 7.5: 96 h Pimephales		
	promelas mg/L LC50 static		
	6.2 - 9.6: 96 h Pimephales		
	promelas mg/L LC50		
	8 - 12.5: 96 h Pimephales		
	promelas mg/L LC50 static		
	9.9 - 20.1: 96 h Brachydanio		
	rerio mg/L LC50 semi-static		
	1.31: 96 h Cyprinus carpio		
	mg/L LC50 semi-static		
	4.2: 96 h Oncorhynchus		
	mykiss mg/L LC50		
	4.5: 96 h Lepomis		
	macrochirus mg/L LC50		
	4.62: 96 h Oncorhynchus		
	mykiss mg/L LC50		
	flow-through		
	7.97: 96 h Brachydanio rerio		
	mg/L LC50 flow-through		
2-Butoxyethanol	1490: 96 h Lepomis	10	000: 48 h Daphnia magna
111-76-2	macrochirus mg/L LC50		mg/L ĖC50
	static		0
	2950: 96 h Lepomis		
	macrochirus mg/L LC50		
Sodium Lauroyl Sarcosinate	107: 96 h Danio rerio mg/L		
137-16-6	LC50		

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
N-Butane	2.89
106-97-8	
Sodium Lauryl Sulfate	1.6
151-21-3	
Propane	2.3
74-98-6	
2-Butoxyethanol	0.81
111-76-2	

Other adverse effects

No information available

13. Disposal Considerations		
Waste treatment methods		
Disposal of wastes	Dispose of in accordance with federal, state and local regulations.	
Contaminated packaging	Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.	

14. Transport Information

DOT UN/ID no

Limited Quantity

Proper Shipping Name	Consumer Commodity
Hazard Class	NA

IATA UN/ID no Proper Shipping Name Hazard Class	UN1950 Aerosols, flammable 2.1
IMDG	
UN/ID no	UN1950
Proper Shipping Name	Aerosols, flammable
Hazard Class	2.1

15. Regulatory information

International Inventories TSCA

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Subtances Control Act (TSCA) Chemical Substance Inventory. All ingredients are listed or are excluded from listing on the DSL.

DSL

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product does not contain toxic chemicals (above the de minimis level) subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
2-Butoxyethanol - 111-76-2	111-76-2	<1	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			Х
N-Butane 106-97-8	Х	Х	Х
Propane 74-98-6	Х	Х	Х
2-Butoxyethanol 111-76-2	Х	Х	Х

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information						
NFPA	Health Hazards 2	Flammability 1	Instability 1	Physical and chemical properties Not applicable		
<u>HMIS</u>	Health Hazards 2	Flammability 2	Physical hazards 1	Personal Protection B - Eyes and hands protection		
Prepared by Issue date Revision note	Regulatory Department 04-Apr-2023					

This SDS supersedes a previous SDS dated: 09-Dec-2020

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet